

Foaming Hypocleanser Nowchem

Version No: **2.4**Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 06/01/2016 Revision Date: 11/01/2021 L.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Foaming Hypocleanser	
Chemical Name	Not Applicable	
Synonyms	Not Available	
Proper shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (contains sodium hypochlorite and sodium hydroxide)	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet

Registered company name	Nowchem	
Address	112A Albatross Road NSW Australia	
Telephone	2) 4421 4099	
Fax	(02) 4421 4932	
Website	www.nowchem.com.au	
Email	sales@nowchem.com.au	

Emergency telephone number

Association / Organisation	Nowchem
Emergency telephone numbers	(02) 4421 4099
Other emergency telephone numbers	0413 809 255

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

	Min	Max	
Flammability	0		
Toxicity	0		0 = Minimum
Body Contact	3		1 = Low
Reactivity	0		2 = Moderate
Chronic	0		3 = High 4 = Extreme

Poisons Schedule	Not Applicable	
Classification ^[1]	Classification [1] Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Version No: 2.4 Page 2 of 12

Foaming Hypocleanser

Issue Date:06/01/2016
Revision Date: 11/01/2021







Signal word

Danger

Hazard statement(s)

H290	May be corrosive to metals.	
H314	Causes severe skin burns and eye damage.	
H335	May cause respiratory irritation.	

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P280	P280 Wear protective gloves/protective clothing/eye protection/face protection.	
P234	Keep only in original container.	

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P305+P351+P338	P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER or doctor/physician.	
P321	P321 Specific treatment (see advice on this label).	
P363 Wash contaminated clothing before reuse.		
P390 Absorb spillage to prevent material damage.		
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.		

Precautionary statement(s) Storage

	_ -	
P405	Store locked up.	
P403+P233	P403+P233 Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
61788-90-7	<10	(C12-14)alkyldimethylamine oxide
10022-70-5	<10	sodium hypochlorite
12200-64-5	<10	sodium hydroxide

SECTION 4 First aid measures

Description of first aid measures

If this product comes in contact with the eyes:

Immediately hold eyelids apart and flush the eye continuously with running water.

- Eye Contact

 Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Version No: 2.4 Page 3 of 12

Foaming Hypocleanser

Revision Date: 11/01/2021

Issue Date:06/01/2016

Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short-term repeated exposures to highly alkaline materials

- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

▶ Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- ▶ Neutralising agents should never be given since exothermic heat reaction may compound injury.
- * Catharsis and emesis are absolutely contra-indicated.
- * Activated charcoal does not absorb alkali.
- * Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- ▶ If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

For acute or repeated exposures to hypochlorite solutions:

- PRelease of small amounts of hypochlorous acid and acid gases from the stomach following ingestion, is usually too low to cause damage but may be irritating to mucous membranes. Buffering with antacid may be helpful if discomfort is evident.
- Evaluate as potential caustic exposure.
- ▶ Decontaminate skin and eyes with copious saline irrigation. Check exposed eyes for corneal abrasions with fluorescein staining.
- ▶ Emesis or lavage and catharsis may be indicated for mild caustic exposure.
- Chlorine exposures require evaluation of acid/base and respiratory status.
- Inhalation of vapours or mists may result in pulmonary oedema.

ELLENHORN and BARCELOUX: Medical Toxicology.

Excellent warning properties force rapid escape of personnel from chlorine vapour thus most inhalations are mild to moderate. If escape is not possible, exposure to high concentrations for a very short time can result in dyspnea, haemophysis and cyanosis with later complications being tracheobroncho-pneumonitis and pulmonary oedema. Oxygen, intermittent positive pressure breathing apparatus and aerosolysed bronchodilators are of therapeutic value where chlorine inhalation has been light to moderate. Severe inhalation should result in hospitalisation and treatment for a respiratory emergency.

Any chlorine inhalation in an individual with compromised pulmonary function (COPD) should be regarded as a severe inhalation and a respiratory emergency. [CCINFO, Dow 1988] Effects from exposure to chlorine gas include pulmonary oedema which may be delayed. Observation in hospital for 48 hours is recommended

Diagnosed asthmatics and those people suffering from certain types of chronic bronchitis should receive medical approval before being employed in occupations involving chlorine exposure.

If burn is present, treat as any thermal burn, after decontamination.

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.

(ICSC24419/24421

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- ▶ Foam
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Advice for firefighters

Version No: 2.4 Page 4 of 12

Foaming Hypocleanser

Issue Date:06/01/2016 Revision Date: 11/01/2021

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit corrosive fumes.
HAZCHEM	2X

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or	r disposal of
material.	

- ▶ Check regularly for spills and leaks.
- ► Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
 Contain and absorb spill with sand, earth, inert material or vermiculite.
- ▶ Wipe up.
- Place in a suitable, labelled container for waste disposal.

Chemical Class: bases

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
-----------------	------	-------------	------------	-------------

LAND SPILL - SMALL

cross-linked polymer - particulate	1	shovel	shovel	R,W,SS
cross-linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R, I, P
foamed glass - pillow	2	throw	pitchfork	R, P, DGC, RT
expanded minerals - particulate	3	shovel	shovel	R, I, W, P, DGC
foamed glass - particulate	4	shovel	shovel	R, W, P, DGC,

LAND SPILL - MEDIUM

cross-linked polymer -particulate	1	blower	skiploader	R,W, SS
sorbent clay - particulate	2	blower	skiploader	R, I, P
expanded mineral - particulate	3	blower	skiploader	R, I,W, P, DGC
cross-linked polymer - pillow	3	throw	skiploader	R, DGC, RT
foamed glass - particulate	4	blower	skiploader	R, W, P, DGC
foamed glass - pillow	4	throw	skiploader	R, P, DGC., RT

Major Spills

Legend

DGC: Not effective where ground cover is dense

R: Not reusable I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear full body protective clothing with breathing apparatus.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- ▶ Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- ▶ Neutralise/decontaminate residue (see Section 13 for specific agent).
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.

Version No: 2.4 Page 5 of 12

Foaming Hypocleanser

Issue Date:06/01/2016
Revision Date: 11/01/2021

- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with moisture.
- Avoid contact with incompatible materials.
- When handling, **DO NOT** eat, drink or smoke
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Other information

Safe handling

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- DO NOT store near acids, or oxidising agents
- No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container

Liquid inorganic hypochlorites shall not to be transported in unlined metal drums. Inner packagings shall be fitted with vented closures and plastics drums and carboys shall have vented closures or be performance tested to a minimum of 250 kPa. All non-vented packagings shall be filled so that the ullage is at least 10% at 21-25 deg.C. Vented packagings may be filled to an ullage not less than 5% at 21-25 deg.C, provided that this ullage does not result in leakage from, nor distortion of, the packaging.

- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer (HDPE).
- ► Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

Presence of rust (iron oxide) or other metal oxides catalyses decomposition of inorganic hypochlorites.

- Contact with water can cause heating and decomposition giving off chlorine and oxygen gases. Solid hypochlorites in contact with water or moisture may generate sufficient heat to ignite combustible materials. Thermal decomposition can be sustained in the absence of oxygen.
- ► Contact with acids produces toxic fumes of chlorine.
- Inorganic hypochlorites reacts violently with many incompatible materials including fuels, oils, wood, paper, etc. which become readily ignitable. Avoid contact with peroxides glycerine, lubricating oil, combustibles, amines, solvents, charcoal, metal oxides and salts, copper, mercaptan, sulfur, organic sulfides, turpentine.
- Contact of hypochlorites with nitromethane, alcohols, glycerol, phenol or diethylene glycol monomethyl ether results in ignition.
- Ammonia or primary aliphatic or aromatic amines may react with hypochlorites to form N-mono- or di-chloramines which are explosively unstable (but less so than nitrogen trichloride). Contact in drains between effluents containing ammonium salts and hypochlorites and acid lead to the formation of nitrogen trichloride which decomposed explosively. Whilst cleaning a brewery tank, reaction between an acidified ammonium sulfate cleaning preparation and sodium hypochlorite, lead nitrogen chloride formation and violent explosion
- Interaction of ethyleneimine (aziridine) with hypochlorites gives an explosive N-chloro compound
- Interaction of metal hypochlorites with nitrogenous materials may lead to the formation of nitrogen trichloride with explosive decomposition.
- ▶ Metal oxides catalyse the oxygen decomposition of the hypochlorite
- Heating with carbon under confinement can result in explosion. Explosive interaction has occurred with carbonised food residues. After an attempt to clean these using bleach, and after heating, sodium chlorate appears to have been formed with consequent violent explosion
- PRemoval of formic acid from industrial waste streams with sodium hypochlorite solutions produced explosion at 55 deg. C.
- Explosions following reaction with methanol are attributed to formation of methyl hypochlorite.
- When finely divided materials such as sugar, wood dust and paper are contaminated with hypochlorite solution they burn more readily when dry.
- Incompatible with sanitising bowl cleaners containing bisulfites.
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- Avoid contact with copper, aluminium and their alloys.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

Storage incompatibility

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	sodium hydroxide	Sodium hydroxide	Not Available	Not Available	2 mg/m3	Not Available

Emergency Limits

Ingredient Material name TEEL-1 TEEL-2 TEEL-3

Version No: 2.4 Page 6 of 12

Foaming Hypocleanser

Issue Date:06/01/2016 Revision Date: 11/01/2021

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
sodium hypochlorite	Sodium hypochlorite pentahydrate	13 mg/m3	140 mg/m3	290 mg/m3
sodium hypochlorite	Sodium hypochlorite	2 mg/m3	290 mg/m3	1,800 mg/m3
sodium hydroxide	Sodium hydroxide	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
(C12-14)alkyldimethylamine oxide	Not Available	Not Available
sodium hypochlorite	Not Available	Not Available
sodium hydroxide	10 mg/m3	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
(C12-14)alkyldimethylamine oxide	E	≤ 0.01 mg/m³		
sodium hypochlorite	C > 0.1 to ≤ milligrams per cubic meter of air (mg/m³)			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- ▶ cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Exposure controls

ı	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can
ı	be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
ı	The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Appropriate engineering controls

Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area

Personal protection









- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalentl

Skin protection

See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

Hands/feet protection

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Body protection

See Other protection below

Version No: 2.4 Page 7 of 12

Foaming Hypocleanser

Issue Date: 06/01/2016
Revision Date: 11/01/2021

Other protection

- Overalls.
- ► PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear Yellow Liquid		
Physical state	Liquid	Relative density (Water = 1)	1.08 - 1.10
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	>12	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Non Flammable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhaled

Inhalation of alkaline corrosives may produce irritation of the respiratory tract with coughing, choking, pain and mucous membrane damage. Pulmonary oedema may develop in more severe cases; this may be immediate or in most cases following a latent period of 5-72 hours. Symptoms may include a tightness in the chest, dyspnoea, frothy sputum, cyanosis and dizziness. Findings may include hypotension, a weak and rapid pulse and moist rales.

The material has **NOT** been classified by EC Directives or other classification systems as 'harmful by inhalation'. This is because of the lack of corroborating animal or human evidence. In the absence of such evidence, care should be taken nevertheless to ensure exposure is kept to a minimum and that suitable control measures be used, in an occupational setting to control vapours, fumes and aerosols.

Ingestion

The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.

The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Version No: 2.4 Page 8 of 12

Foaming Hypocleanser

Issue Date:06/01/2016
Revision Date: 11/01/2021

Ingestion of hypochlorites may cause burning in the mouth and throat, abdominal cramps, nausea, vomiting, diarrhoea, pain and inflammation of the mouth and stomach, fall of blood pressure, shock, confusion, and delirium. Severe poisonings may lead to convulsion, coma and death. Ingestion irritates the mouth, throat, and stomach. The hypochlorous acid liberated in the stomach can cause wall perforation, toxemia, haemorrhage and death.

Necrosis and haemorrhage of the upper digestive tract, oedema and pulmonary emphysema were found on autopsy after suicidal ingestion, and methaemoglobinaemia was also reported in another fatal case

The material can produce chemical burns following direct contact with the skin.

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Contact may cause severe itchiness, skin lesions and mild eczema.

Skin Contact

A 5.25% solution of sodium hypochlorite applied to intact human skin for 4 hours and observed at 4, 24 and 48 hours resulted in exudation an slight sloughing of the skin on 4 of 7 subjects.

Two patients were reported with chronic allergic dermatitis of the hand related to sensitisation to sodium hypochlorite as the active component of laundry bleach

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye

The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Hypochlorite in pool water at concentrations of 1 ppm chlorine or less is non irritating to eyes if the pH is higher than 7.2 (slightly alkaline). At lower pH, a sensation of stinging, smarting of eyes with transient reddening may occur but generally no injury.

Eye contact with a 5% hypochlorite solution may produce a temporary burning discomfort and slight irritation of the corneal epithelium with no injury

Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population.

Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.

Chronic

There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

Reduced respiratory capacity may result from chronic low level exposure to chlorine gas. Chronic poisoning may result in coughing, severe chest pains, sore throat and haemoptysis (bloody sputum). Moderate to severe exposures over 3 years produced decreased lung capacity in a number of workers.

Delayed effects can include shortness of breath, violent headaches, pulmonary oedema and pneumonia.

Amongst chloralkali workers exposed to mean concentrations of 0.15 ppm for an average of 10.9 years a generalised pattern of fatigue (exposures of 0.5 ppm and above) and a modest increased incidence of anxiety and dizziness were recorded. Leukocytosis and a lower haematocrit showed some relation to exposure.

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Foaming Hypocleanser

TOXICITY	IRRITATION
Not Available	Not Available

(C12-14)alkyldimethylamine oxide

TOXICITY	IRRITATION
Inhalation(Mouse) LC50 0.6 mg/l/4hd ^[2]	Not Available
Oral(Rat) LD50 >2000 mg/kg ^[2]	
Oral(Rat) LD50 4610 mg/kg ^[2]	

sodium hypochlorite

TOXICITY	IRRITATION
240 mg/kg ^[2]	Eye (rabbit): 10 mg - moderate
Oral(Rat) LD50 >5000 mg/kg ^[2]	Eye (rabbit): 100 mg - moderate
	Skin (rabbit): 500 mg/24h-moderate

sodium hydroxide

TOXICITY	IRRITATION	
~500 mg/kg ^[2]	Eye (rabbit): 0.05 mg/24h SEVERE	
	Eye (rabbit):1 mg/24h SEVERE	
	Eye (rabbit):1 mg/30s rinsed-SEVERE	
	Eye: adverse effect observed (irritating) ^[1]	
	Skin (rabbit): 500 mg/24h SEVERE	
	Skin: adverse effect observed (corrosive) ^[1]	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Version No: 2.4 Page 9 of 12

Foaming Hypocleanser

×

Issue Date:06/01/2016

Revision Date: 11/01/2021

Acute Toxicity	X	Carcinogenicity	X
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

– Data available to make classification

SECTION 12 Ecological information

Toxicity

F	Endpoint	Test Duration (hr)		r)	Species	Val	ue	So	urce	
Foaming Hypocleanser Not Available			Not Available		Not Available	able Not Available		No	Not Available	
	Endpoint	Tes	t Duration (hr)	s	pecies			Value		Source
	LC50	96		F	ish			2.67mg/L		2
12-14)alkyldimethylamine	EC50	48		С	rustacea			2.9mg/L		2
oxide	EC50	72		А	lgae or other aquatic pla	ants		0.015mg/L		2
	EC10			ants		0.002mg/L		2		
	NOEC			А	Algae or other aquatic plants			0.003mg/L		2
	Endpoint	Test	Duration (hr)	Specie	es		Value			Source
	LC50			Fish	Fish >0		>0.023-	0.023-<0.052mg/L		4
sodium hypochlorite	EC50			Crusta	cea	0.01mg/		Ľ		4
	EC50	72		Algae	or other aquatic plants		0.018mg		g/L	
	NOEC	72	2 Al		ae or other aquatic plants 0.005mg			/L 2		2
	Endpoint		Test Duration (hr)		Species Value			Sou		ource
sodium hydroxide	LC50	96			Fish	125mg	125mg/L		4	
	EC50	48			Crustacea -34.59-4		.59-47.13mg/L 4			

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For chlorine:

Environmental fate:

Atmospheric chlorine produced as a result of such process as disinfection forms hydrochloric (HCl) or hypochlorous (HOCl) acid in the atmosphere, either through reactions with hydroxy radicals or other trace species such as hydrocarbons. These acids are believed to removed from the atmosphere primarily through precipitation washout (i.e. wet deposition as chlorine is scrubbed out by rain in the subcloud layer) or dry deposition as gaseous chlorine contacts and reacts with the earths surface.

Water chlorination, resulting from municipal and industrial wastewater treatment and cooling water disinfection, initially introduces chlorine into the water as chlorine gas, hypochlorite ion (OCI-), or its salt. These forms of chlorine are termed free residual chlorines (FRC). Chlorine in aqueous systems volatilises or quickly decays to residual forms such as hypochlorous acid, chloramine and chlorinated organics. Aquatic chemistry is determined by aquatic factors including pH, ammonium ion (which combines with chlorine to produce chloramine) and certain other reducing agents. Inorganic reducing agents in estuarine waters include sulfur, iron and manganese. Other organic compounds in water also contribute to chlorine decay rate. The reactions of chlorine or hypochlorites in water produce a number of by-products many of which have been implicated as genotoxic or tumourigenic. Chlorine, added to drinking water as chlorine gas (Ci2) or hypochlorite salts (e.g., NaOCI), effectively inactivates bacteria in 20 minutes at concentrations of 0.03 to 0.06 mg/l at pH range of 7.0 to 8.5 and temperature range of 4 deg.C to 22 deg.C.

Chlorine disinfectants in wastewater react with organic matters, giving rise to organic chlorine compounds such as AOX (halogenated organic compounds absorbable on activated carbon), which are toxic for aquatic organisms and are persistent environmental contaminants.

Chlorine hydrolyses very rapidly in water (rate constants range from 1.5×10 -4 at deg. C to 4.0×10 -4 at 25 deg.C; half-life in natural waters, 0.005 seconds. In fresh and wastewaters at pH >6, complete hydrolysis occurs with the formation of hypochlorous acid (HOCI) and chloride ion (CI-). The hypochlorous acid ionizes to hydrogen ion (H+) and hypochlorite ion (OCI-). At pH values >5, OCI- predominates; at pH values <5, HOCI predominates. Free chlorine (CI2, HOCI, and OCI-) reacts rapidly with inorganics such as bromide and more slowly with organic material present in natural waters. These reactions yield chloride, oxidised organics, chloroorganics (including trihalomethanes), oxygen, nitrogen, chlorate, bromate and bromoorganics.

Chlorines ultimate aqueous fate is chloride.

Vapourisation of molecular chlorine (Cl2) from water to the atmosphere may be significant at low pH values and high concentrations (e.g., pH 2 and 3500 mg/l chlorine), but is insignificant at neutral pH and low concentrations.

Vegetation acts as an important sink for chlorine air pollution. Plant exposure to elevated levels of chlorine can cause plant injury; however chlorine tends to be rapidly converted to other less toxic forms.

Atmospheric: When chlorine, hypochlorous acid or hydrogen chloride mixes in the atmosphere with water vapour, dilute solutions of strong mineral acids are formed that fall to earth as acid rain, snow, and fog, or acidified dry particles.

Chlorine may react with soil components to form chlorides; depending on their water solubility, these chlorides are easily washed out from the soil.

Bioaccumulation/ bioconcentration: There is no potential for the bioaccumulation or bioconcentration of chlorine.

Ecotoxicity:

Fish LC50 (96 h): 0.015-13.5 mg/l

Chlorine has high acute toxicity to aquatic organisms; many toxicity values are less than or equal to 1 mg/l. Twenty-four-hour LC50 values range from 0.076 to 0.16 mg/l for Daphnia magna (water flea) and from 0.005 to 0.1 m/l for Daphnia pulex (cladocern); 48-hour LC50 values range from 5.3 to 12.8 m/l for Nitocra spinipes (snail); and 96-hour LC50 values range from 0.13 to 0.29 mg/L for Oncorhynchus mykiss (rainbow trout), from 0.1 to 0.18 mg/l for Salvelinus fontinalis (brook trout), and from 0.71-0.82 mg/l for Lepomis cyanellus (green sunfish)

Papillomas of the oral cavity in fish have been associated with exposure to chlorinated water supplies.

Version No: 2.4 Page 10 of 12

Foaming Hypocleanser

Issue Date: 06/01/2016
Revision Date: 11/01/2021

Chlorine is phytotoxic but is also essential to plant growth; crops need around 2 kg or more of chlorine per acre. Acute toxicity to plants is characterized by defoliation with no leaf symptoms and, in higher plant forms, by spotting of the leaves (at 1.5 mg/m3) and marginal and interveinal injury (at 150-300 mg/m3)

Data from experimental studies indicate that injury to animals occurs only in the presence of high concentrations of chlorine, either in drinking water or the ambient atmosphere. http://www.epa.gov/chemfact/s chlori.txt

U.S. ENVIRONMENTAL PROTECTION AGENCY August 1994

for hypochlorites:

Environmental fate:

NOTE: Hypochlorite ion is predominant at alkaline pH values, while Cl2 is mainly present at pH below 4. Therefore the concentration of chlorine in an aqueous solution is generally expressed as free available chlorine (FAC) which is the sum of Cl2 + HOCl + ClO-, regardless whether these species stem from dissolved gaseous chlorine or from dissolved sodium/calcium hypochlorite

Hypochlorite anion dissolved in water is brought to equilibrium between active chlorine species like chlorine (Cl2), hypochlorous acid (HOCl) or hypochlorite ClO-. The relative amounts of the components are dependent on ionic strength and pH. At the pH in the natural environment (6-8), HOCl or ClO is dominating (HClO: pKa = 7.53). A diluted aqueous solution of HOCl will decompose very slowly in the dark, but more rapidly in the presence of light, particularly rapidly in full sun light, by producing hydrogen chloride and oxygen. Some chlorine and chloric acid (HClO3) may also develop. The physico-chemical properties indicate that chlorine released into the environment as HClO or Cl2 is distributed into water and air. Consequently, the effects that may manifest in the natural environment are considered common to those assessed for the other source of hypochlorite.

In the natural water, in the presence of organic or inorganic compounds, the free available chlorine immediately reacts forming various chlorinated and/or oxidized by-products e.g. chloramines or chloromethanes. They are mainly distributed to the hydrosphere, but are also able to transfer to some extent to the atmosphere depending on their intrinsic properties. A potential for bioaccumulation or bioconcentration of active chlorine species can be disregarded, because of their water solubility and their high reactivity.

In fresh water, the hypochlorites break down rapidly into non-toxic compounds when exposed to sunlight. In seawater, chlorine levels decline rapidly; however, hypobromite (which is acutely toxic to aquatic organisms) is formed. Sodium and calcium hypochlorite are low in toxicity to avian wildlife, but they are highly toxic to freshwater fish and invertebrates. Hypochlorite is a highly reactive chemical which, during and after its use in household scenarios, undergoes a variety of reactions. The major one is the oxidation of inorganic and organic species.

A minor reaction, which consumes about 1.5% of the chlorine atoms from hypochlorite, is chlorination, which leads to formation of organohalogen by-products that are often measured by the group parameter, AOX.

Hypochlorite itself is rapidly broken down during use, in the sewer, and if any does reach sewage treatment it will further degrade (half-life of around 0.6 minutes). Predictions have indicated that its concentration will fall to below 1.E-32 ug/l by the end of the sewer, partially due to its reaction with ammonia in the sewer which leads to a subsequent increase in chloramine.

The organohalogen by-products formed from the use of hypochlorite are currently receiving much attention. However, the levels of AOX produced are low (for example, 37 ug/l from bleach use compared to a sewage background level of 106 ug/l), and the organohalogens produced from domestic use of hypochlorite are not believed to have an adverse effect on the environment. Available data indicate that no dioxins are produced, and that the identified AOXs are typically small molecules with a low degree of chlorination and for which ecotoxicological properties are known or can be predicted. Where drinking water is disinfected by chlorination, the levels of organohalogens in sewage effluent arising from bleach use will be comparable with, and sometimes only a fraction of, those arising from the tap-water. After secondary sewage treatment, the levels entering receiving waters will be of the same order of magnitude as background levels typically present in rivers, though the total flux in rivers from natural sources will be much greater.

The majority of the measured AOX is unidentified, but thought to consist of high molecular weight components formed from fats, proteins and humic acids which are too large to bioaccumulate.

In addition, studies on the whole AOX mixture in laundry waste-water indicated that the level of AOX present did not effect growth or reproduction of *Ceriodaphnia*, and that around 70% is removed in activated sludge.

Ecotoxicity:

The level of chloramine reaching surface water is estimated to be below 5.E-10 ug/l. Both these concentrations are orders of magnitude below the lowest acute EC50s determined for sodium hypochlorite (EC50 to invertebrates = 5 ug/l) and monochloramine (EC50 to invertebrates = 16 ug/l).

Valid freshwater short-term toxicity data are available only for invertebrates: the LC50 for Ceriodaphnia dubia is 5 ug FAC/I (FAC=Free available chlorine). Adequate standard acute tests in fish are not available, but from many reliable studies performed under intermittent exposure conditions a 96h LC50 of 60 ug TRC/L and a 168 h LC50 of 330 ug TRC/L can be derived (TRC = total residual chlorine = the sum of combined and free residual available chlorine). Due to the intermittent regime (three 45 minutes pulses per day) a 96h LC50 << 60 ug TRC/l can be expected for fish in a standard test. Most lowest result for algae is reported for Thalassiosira pseudonana with a IC50 of 75 ug/L (20 deg C).

Regarding long-term toxicity to freshwater organisms, the lowest NOEC was 5 ug/L (Ictalurus punctatus, 133 d, growth). In microcosm and field studies the most sensitive parameter was the density of zooplankton with a NOEC of 1.5 ug TRC/L, and zooplankton is more sensitive to chlorine than algae.

For salt water, valid short-term toxicity data are available for mollusks and for fish (Oncorhynchus kisutch 96 h LC50 = 32 ug TRO/L) (TRO = Total Residual Oxidant) showing comparable sensitivity. For long term toxicity the molluscs are more sensitive than fish showing a 15 d NOEC of 6.2 ug TRO/L. It is impossible to delineate representative toxicity indicator figures because of the unique feature of the chemical to be tested in standard methods. However, the accumulated scientific information covering a wide range of species, temperature application regime or field studies can be used for the hazard assessment.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
(C12-14)alkyldimethylamine oxide	LOW	LOW
sodium hydroxide	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
(C12-14)alkyldimethylamine oxide	HIGH (LogKOW = 4.673)
sodium hydroxide	LOW (LogKOW = -3.8796)

Mobility in soil

Ingredient	Mobility
(C12-14)alkyldimethylamine oxide	LOW (KOC = 18660)
sodium hydroxide	LOW (KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ► Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Treat and neutralise at an approved treatment plant.

Version No: 2.4 Page 11 of 12

Foaming Hypocleanser

Issue Date:06/01/2016 Revision Date: 11/01/2021

- Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 Transport information

Labels Required



Marine Pollutant
HAZCHEM

NO 2X

Land transport (ADG)

UN number	3266	3266			
UN proper shipping name	CORROSIVE LIQUID,	BASIC, INORGANIC, N.O.S. (contains sodium hypochlorite and sodium hydroxide)			
Transport hazard class(es)	Class 8 Subrisk Not Appl	licable			
Packing group	Ш				
Environmental hazard	Not Applicable				
Special precautions for user	Special provisions Limited quantity	223 274 5 L			

Air transport (ICAO-IATA / DGR)

,	- <i>7</i>				
UN number	3266				
UN proper shipping name	Corrosive liquid, basic, ir	Corrosive liquid, basic, inorganic, n.o.s. * (contains sodium hypochlorite and sodium hydroxide)			
	ICAO/IATA Class	8			
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable			
	ERG Code	8L			
Packing group	III				
Environmental hazard	Not Applicable				
	Special provisions		A3 A803		
	Cargo Only Packing Instructions		856		
	Cargo Only Maximum Qty / Pack		60 L		
Special precautions for user	Passenger and Cargo Packing Instructions		852		
	Passenger and Cargo	Maximum Qty / Pack	5 L		
	Passenger and Cargo Limited Quantity Packing Instructions		Y841		
	Passenger and Cargo Limited Maximum Qty / Pack		1 L		
]				

Sea transport (IMDG-Code / GGVSee)

UN number	3266	
UN proper shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (contains sodium hypochlorite and sodium hydroxide)	
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk N	lot Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number Special provisions Limited Quantities	F-A , S-B 223 274 5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Version No: 2.4 Page 12 of 12

Foaming Hypocleanser

Issue Date:06/01/2016
Revision Date: 11/01/2021

(C12-14)alkyldimethylamine oxide is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

sodium hypochlorite is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule $\bf 6$

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

sodium hydroxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No ((C12-14)alkyldimethylamine oxide; sodium hypochlorite; sodium hydroxide)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No ((C12-14)alkyldimethylamine oxide)	
Vietnam - NCI	Yes	
Russia - ARIPS	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 Other information

Revision Date	11/1/2021
Initial Date	09/11/2015

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.